

# MSL

# S63

## Adhesive for soundproofing membranes, engineered wood, parquet and vinyl flooring

### PRODUCT DESCRIPTION

MSL S63 is a solvent free adhesive with superior bonding performance for the installation of soundproofing membranes, vinyl planks, engineered hard wood floors and wood parquet, including exotic woods on cured concrete, T&G plywood or subfloor agglomerate boards. MSL S63 is also designed to be used to bond parquet or vinyl planks on support or soundproofing membranes.

### PRODUCT HIGHLIGHTS

- For soundproofing membranes
- For vinyl planks
- For all types of wood flooring
- Superior bonding performance
- Solvent free

### PREPARATION

Subfloor must be structurally sound, linear, porous, clean, dry and free of contaminants. The adhesive and the flooring material (unwrapped) must be at room temperature (20° C) 24 hours prior to, during and following installation. For best results, moisture content of the wood should ideally range between 8% and 12%; concrete must be completely cured, and free from moisture and hydrostatic pressure.

For additional information :  
Customer support : 1 (800) 561-4279  
Website : [www.mslfibre.com](http://www.mslfibre.com)

[infoplus@mslfibre.com](mailto:infoplus@mslfibre.com)

Developed in  
**Canada**



### PROPERTIES

Viscosity	70 – 75 M cps
Solids	76 +/- 1.5%
Colour	Green
Odour	Mild
Specific Gravity	1.15 +/- 0.02
pH	7.5 – 8.5
Water Resistance	Excellent (when dry)
Open Time	20 minutes
VOC	<50 g/L
Flash Point	None

### COVERAGE

Approximately 1.8 m<sup>2</sup> / L (V notch trowel - 3/16")

### ATTENTION

Refer to flooring and/or soundproofing membrane manufacturer's recommendations for expansion space requirements and detailed installation instructions. Room temperature must be kept at 20°C and at relative humidity between 35%-55% one week before the installation and thereafter. For indoor use only. For basement floors or areas below grade, a subfloor should be built over a vapour barrier.

### RESTRICTIONS

Do not use on floors with radiant heat systems.

### CLEANING

Wash hands, tools as well as excess adhesive with warm soapy water before product dries. If adhesive has dried, clean cautiously with a mineral spirits. On bonded materials, scrape and sand excess adhesive.

### STORAGE

Shelf life of this product is 1 year in original unopened container stored at room temperature. This product is stable from freeze/thaw to -10 degrees C.

### PRECAUTIONS

This product is not classified dangerous as per the Consumer Chemicals and Containers Regulations (CCCR). Not a regulated product as per the Workplace Hazardous Materials Information System (WHMIS). For further details, see Material Safety Data Sheet.

### ENVIRONMENT

Meets VOC standards for low emissions adhesives and sealants in place at date of production.

### PACKAGING

Size	Units per Package	Units per Row	Units per Pallet
15.0L	1	12	48

### WARRANTY

Surface conditions, application, storage and transportation of product are not in the manufacturer's control; any liability is strictly limited to product replacement.