



SONOVIB features

- High performance acoustic membrane designed to attenuate impact noise for glued wood floors, floating wood floors, vinyl and carpet
- Continuous sound insulation
- Decoupling membrane
- Water repellent
- Stable dimensions
- Light and easy to install
- Antimicrobial

**Scope: GLUED WOOD FLOORS, FLOATING WOOD FLOORS
VINYL AND CARPET**

Properties	Requirements	Nominal Value
Acoustic FIIC	ASTM E-1007-04 ASTM E-989-06	FIIC 57 to 68
Compression Strength (10% def.)	ASTM D3575-20 suffix D	0.135 PSI 0.01 kg / cm ²
Compression Strength (25% def.)	ASTM D3575-20 suffix D	0.97 PSI 0.07 kg / cm ²

Physical Properties	Metric	Imperial
Density:	123.84 kg / m ³	7.73 lbs / ft ³
Roll size:	1.47 m x 15.24 m	58 in x 50 ft
Area covered / roll:	22.45 m ²	241.67 ft ²
Thickness:	2.62 mm	0.1031 in
Weight / roll:	7.8 kg	17.2 lbs
Number of rolls / skid:	25 rolls	

Ecological Properties

0 % - COV (g. / l.) - Volatile organic compounds

100% recycled polyester fibre

For additional information:
Customer support: 1 800 561 4279
Web site: www.mslfibre.com

info@mslfibre.com

Developed in
Canada 